

NITTERHOUSE

MASONRY PRODUCTS, LLC

WIND UPLIFT CONNECTION

DESIGNED FOR USE WITH
OUR HIDDEN FASTENING
KIT & PEDESTALS



NITTERHOUSE PAVERS WITH WIND UPLIFT CONNECTION

WIND UPLIFT RESISTANCE: 350 psf *(fully adhered systems-contact for details)*

COMPRESSION STRENGTH: Avg 8500 psi

WATER ABSORPTION: Less than 5% *(ASTM C140)*



← Nitterhouse Hydraulic Pressed Paver

← Nitterhouse Paver Fastening Kit

← Nitterhouse Pedestal

Nitterhouse's Wind Uplift Connection pavers have an innovative slot in each corner allowing for a special washer and finishing screw to be inserted. After all pavers are placed, the Nitterhouse Tie Down System is undetectably screwed into the corresponding reinforced top of the Nitterhouse pedestal to securely lock down the pavers ensuring a safe, secure and level surface.

NITTERHOUSE PEDESTAL

| | |
|---------------------------|--|
| MATERIAL | Polypropylene and rubber (head top) |
| HEIGHT | 1" - 39" |
| BASE DIAMETER & THICKNESS | 8" x 1/16" |
| HEAD DIAMETER | 7" |
| BASE CONTACT SURFACE AREA | 49 in ² |
| TAB HEIGHT & THICKNESS | 1/2" x 5/32" |
| COMPRESSION STRENGTH | > 3,000 PSF |
| FIRE RATING | Class E (UNI EN 13501-1: 2009) |
| CHARACTERISTICS | Adjustable height Security lock to prevent unlocking Recyclable material |



Pedestal works with all Nitterhouse Architectural & Camina Paving Stones



NITTERHOUSE

MASONRY PRODUCTS, LLC