

# NITTERHOUSE



## **SPECIFICATIONS FOR: CONCRETE FENCE POSTS**

### **MATERIALS**

Manufactured precast concrete conforming to the following ASTM specifications:

- Type 1 Portland Cement- ASTM C-150
- Fine and Coarse Aggregate- ASTM C-33
- Steel Reinforcing shall conform to ASTM A-185; A-615
- Steel Anchoring pins conform to ASTM A-185; A-615

### **TECHNICAL DATA**

Nitterhouse Masonry Products, LLC precast concrete fence posts shall meet the following specifications:

- 5,500 PSI minimum compressive strength
- 6.0% maximum absorption rate
- Steel Reinforced

Finish: High frequency vibration zero slump concrete, Dry Cast-Steel Form Finish

Sizing:

2 Rail- 7-1/2" x 7-1/2" x 59"

3 Rail- 7-1/2" x 7-1/2" x 83"

### **WARRANTY**

Nitterhouse Masonry Products, LLC products are warranted to be manufactured free of defects in workmanship and materials under normal use for a period of one (1) year after date of delivery.

Repair or replacement of defective products at the option of NMP shall be the sole remedy of this warranty.

### **MANUFACTURER QUALIFICATIONS**

As manufactured by Nitterhouse Masonry Products, LLC

859 Cleveland Ave. Chambersburg, PA 17201

Phone: 717-267-4500

email: [masonry@nitterhouse.com](mailto:masonry@nitterhouse.com)

[www.nitterhousemasonry.com](http://www.nitterhousemasonry.com)