

NITTERHOUSE MASONRY PRODUCTS SPECIFICATIONS FOR: NITTERHOUSE VENEER STONE

PART 3 – EXECUTION

3.01 EXAMINATION

- A. Examine substrates upon which work will be installed.
- B. Coordinate with responsible entity to perform corrective work on unsatisfactory substrates.
- C. Commencement of work by installer is acceptance of substrate.

3.02 PREPARATION

- A. Protection: Protect adjacent work from contact with mortar.
- B. Surface Preparation: Prepare substrate in accordance with manufacturer's installation instructions for the type of substrate being covered.

3.03 INSTALLATION

- A. Install and clean stone in accordance with manufacturer's installation instructions for Standard Installation (Grouted Joint) or Joint less/Dry-Stacked installation as specified above.
- B. Apply sealer in accordance with sealer manufacturer's installation instructions.

3.04 FIELD QUALITY CONTROL

- A. Manufacturer's Field Service Representative shall make site visits for installation consultation as requested by Owner.

3.05 CLEANING IF NECESSARY

- A. Reference Section 01 74 00 (CSI SPEC).
- B. Protect adjacent work during cleaning of veneer.
- C. Cleaning Veneer Units:
 - 1. Wash with soft bristle brush and water/granulated detergent solution.
 - 2. Rinse immediately with clean water.
- D. Removing Efflorescence:
 - 1. Allow veneer to dry thoroughly.
 - 2. Scrub with soft bristle brush and clean water.
 - 3. Rinse immediately with clean water; allow drying
 - 4. If efflorescence is still visible, repeat above procedure using a solution of 1 part Household vinegar and 5 parts water.
 - 5. Rinse immediately with clean water.

END OF SECTION

MANUFACTURER QUALIFICATIONS

As manufactured by Nitterhouse Masonry Products, LLC
859 Cleveland Ave. Chambersburg, PA 17201
Phone: 717-267-4500
email: masonry@nitterhouse.com
www.nitterhousemasonry.com

