

NITTERHOUSE



SPECIFICATIONS FOR: PRECAST CONCRETE PARKING BLOCKS

MATERIALS

Manufactured precast concrete conforming to the following ASTM specifications:

- Type 1 Portland Cement- ASTM C-150
- Fine and Coarse Aggregate- ASTM C-33
- Steel Reinforcing shall conform to ASTM A-185; A-615
- Steel Anchoring pins conform to ASTM A-185; A-615

TECHNICAL DATA

Nitterhouse Masonry Products, LLC precast concrete wheel stops shall meet the following specifications:

- 5,500 PSI minimum compressive strength
- 6.0% maximum absorption rate
- Steel Reinforced
- 6' and 7' lengths are with weep holes

Finish: High frequency vibration zero slump concrete, Dry Cast-Steel Form Finish

Sizing: 6' L x 5" H x 7-5/8" D
7' L x 5" H x 7-5/8" D
8' L x 5" H x 7-5/8" D

WARRANTY

Nitterhouse Masonry Products, LLC products are warranted to be manufactured free of defects in workmanship and materials under normal use for a period of one (1) year after date of delivery.

Repair or replacement of defective products at the option of NMP shall be the sole remedy of this warranty.

MANUFACTURER QUALIFICATIONS

As manufactured by Nitterhouse Masonry Products, LLC
859 Cleveland Ave. Chambersburg, PA 17201
Phone: 717-267-4500
email: masonry@nitterhouse.com
www.nitterhousemasonry.com